



## EXTRA LEED POWER STEERING FLUID

### PRODUCT DESCRIPTION:

Extra Leed Power Steering Fluid is a premium oil specially designed for use in power steering and suspension units. It contains a unique combination of anti-shudder additives, dispersants and seal swell additives along with a specialized base oil to offer maximum wear protection, long service life and minimization of viscosity loss.

### APPLICATION:

Extra Leed Power Steering Fluid is primarily designed and recommended for use in the power steering units of all Honda motor vehicles as well as Rover models 416i, 825 and 827 that use Honda power steering components. It may also be used in high performance applications in other vehicles such as Ford Tickford series, AU, BA & BF XR, FPV & Territory SX-SY series vehicles. The high refined base oils and highviscosity help to reduce pump wear and maintain steering feel where extra heat and load is expected in these applications.

### FEATURES & BENEFITS:

- Correct viscosity for Honda Power Steering units
- Compatible with OEM fluid
- Reduces power steering shudder (noise & chatter)
- Extends seal and hose life
- Multiple use power steering & suspension
- Long Service life
- Protects against rust and corrosion

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Ford M2C134-C
- Ford M2C134-D
- Honda PSF-II
- Honda PSF-S
- Honda PSF-V

### TYPICAL PROPERTIES:

PARAMETERS	ASTM METHOD	UNIT	EXTRA LEED POWER STEERING FLUID
KV@ 104°F /40°C	D7042	cSt	35.89
KV @ 212°F /100°C	D7042	cSt	7.07
Viscosity Index	D2270	-	164
SP. Gravity @15°C	D4052	g/cm3	0.860
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.